

SEARGH

 $\mathbb{N} \cap \mathbb{R}^{\times}$

1/1



PATENT ABSTRACTS OF JAPAN

(11)Publication number: 09080315

(43) Date of publication of application: 28.03.1997

(51)Int.CI.

G02B 21/06

(21)Application number: 07232362

(22)Date of filing: 11.09.1995

(71)Applicant:

YOKOGAWA ELECTRIC CORP

(72)Inventor:

KOSUGI YASUHITO


ISOZAKI KATSUMI

(54) NIPKOW DISK TYPE OPTICAL SCANNER DEVICE

(57) Abstract:

PROBLEM TO BE SOLVED: To eliminate a scan irregularity and obtain an image pickup screen having no light and shade stripe by synchronizing the scan period of the scanner device with the image pickup period of an image pickup device.

SOLUTION: The top surface of a Nipkow disk 20 is irradiated with incident light 1. A multipoint scan on a sample is made with the incident light 1 transmitted through a scan track by rotating this Nipkow disk 20. Incident light I passed through a pinhole for scan start point detection, on the other hand, is photodetected by a photodiode 21 each time the pinhole for scan start point detection passes over a photodiode. At this time, the output current from the photodiode 21 varies in a pulse shape, so this current variation is converted by a current-voltage converting circuit 22 into a voltage, which is inputted to a voltage comparing circuit 23. Consequently, a voltage pulse train having the same period as the scan period can be led out as an output. This pulse train is supplied as a trigger signal to the external image pickup device 25 to synchronize the optical scanner device and image pickup device 25 with each other.





LEGAL STATUS

[Date of request for examination]

17.02.1998

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

3019754

[Date of registration]

07.01.2000

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of

rejection]

[Date of extinction of right]

Copyright (C); 1998 Japanese Patent Office

MENU

SEARCH

INDEX



The Japanese Patent Office is not responsible for any damages caused by the use of this translation.

- 1. This document has been translated by computer. So the translation may not reflect the original precisely.
- 2.**** shows the word which can not be translated.
- 3.In the drawings, any words are not translated.

CLAIMS

[Claim(s)]

[Claim 1] The image of a sample is used for the confocal point microscope constituted possible [an observation] by image pck-up equipment. While it is the Nipkow-disk type light scanner equipment containing the optical scanner fraction equipped with the Nipkow disk and the pinhole for a scanning starting point detection corresponding to the starting point of a scanning truck is arranged on the above-mentioned Nipkow disk Nipkow-disk type light scanner equipment characterized by providing a means to carry out the photo electric translation of the transmitted light of the above-mentioned pinhole for a scanning starting point detection, and to generate the trigger signal for the above-mentioned image pck-up equipment, and enabling it to take a synchronization of a scanning interval and the image pck-up period of image pck-up equipment.

[Claim 2] Nipkow-disk type light scanner equipment according to claim 1 characterized by preparing the micro-lens array disk constituted so that it might be arranged at the incident-light side of the above-mentioned Nipkow disk, it might have the micro-lens array of the pinhole pattern of a Nipkow disk, and the same pattern and a condensing light of each micro lens of a micro-lens array might carry out incidence to the pinhole to which a Nipkow disk corresponds in the above-mentioned optical scanner fraction.

[Translation done.]

0000/00/02	USPAT	4 and 13	90	L14	BRS	15
06/	USPAT	7 and 14	0	L15	BRS	14
06/	USPAT	1 and 12	1332	L13	BRS	13
6/	USPAT	8 and 9	8366	L12	BRS	12
06/	USPAT	1 and 4 and 7	0	Ь11	BRS	 7
)6/	USPAT	1 same 4 same 7	0	L10	BRS	10
)6/	USPAT	scanner	44073	L9	BRS	9
)6/	USPAT	camera	84909	18	BRS	8
2000/06/04 07:57	USPAT	5 adj 6	480	L7	BRS	7
)6/	USPAT	period	776557	L6	BRS	<u>o</u>
)6/	USPAT	rotational	230455	L5	BRS	5
)6/	USPAT	2 adj 3	21848	L4	BRS	4
2000/06/04 07:56	USPAT	time	182032 4	Ľ3	BRS	ω
)6/	USPAT	exposure	225229	L2	BRS	2
)6/	USPAT	comparator	110342	L1	BRS	1-1
Time Stamp	DBs	.Search Text	Hits	#	Туре	

	2000/06/04	USPAT	1 and 8 and 9 and 21	17	L22	BRS	22
	2000/06/04 08:35	USPAT	confocal	2035	L21	BRS	21
	2000/06/04 08:21	USPAT	4 and 19	Φ	L20	BRS	20
·····	2000/06/04 08:21	USPAT	16 17 18	304	L19	BRS	19
·····	2000/06/04 08:21	USPAT	396/116	87	L18	BRS	18
, .	2000/06/04 08:21	USPAT	396/24	92	L17	BRS	17
······	2000/06/04 08:20	USPAT	396/20	132	L16	BRS	16
Com men ts	Time Stamp	DBs	.Search Text	Hits	۲ #	Туре	
			•				

ť

.

					(onts Er	Error Definition
	Type	#	Hits	Search Text	DBS	Time Scamp commence		
					1	2000/05/29		
	BRS	<u> </u>	2030	confocal	USPAT			
					Ϊ	2000/05/29		
2	BRS	L2	56850	microscope	USPAT			
						2000/05/29		
~	BRS	L4	43983	scanner	USPAT			
)					· · · · · ·	2000/05/29	,	
4	BRS	L5	107497	107497 photograph\$3	USPAT			
· 						2000/05/29		
5	BRS	L6	105071	105071 photograp\$3	USPAT			
,					ï	2000/05/29		
٧	BRS	17	145	3 and 4	USPAT			
>						2000/05/29		
7	IRRS	L3	485	1 adj 2	USPAT	14:57		
`_	}							
	***************************************	-						